

Type 1250

Router - DIAMOND COATED - Diamond Cut

Applications / Advantages:

- Ideally suited for routing of inner and outer contours in CFRP, CFP and GRP such as Durostone® and Roedurthem
- Very high dimensional accuracy and process capability due to **thicker diamond coating**



Diamond Coating - Made in Germany

Size mm	Diameter inch	Flute Lengths			
		mm	inch	mm	inch
1.50	.0591	7.5	.295	-	-
1.60	.0630	7.5	.295	-	-
1.80	.0709	8.5	.335	-	-
2.00	.0787	9.0	.354	10.0	.394
2.40	.0945	9.0	.354	10.0	.394
2.50	.0984	9.0	.354	-	-
3.00	.1180	-	-	10.0	.394

Further diameters and flute lengths made to order.

Geometry: 1250

- Thicker diamond coating
- Right hand spiral, right hand cut (up cut)
- Fishtail end style
- Shank diameter .1250" & over-all-length is 1.500".
- Tolerance according to router specifications
- Made of solid carbide

Manufactured by:

GCT, GmbH
Josef-Bayer-Srt.3
D-88250 Weingarten
Germany
Rev- 02/2015

Tel. +49-(0) 751- 50 91 58 0
Fax: +49-(0) 751-50 91 58 99
E-Mail: info@gctool.com
www.gctool.com
Subject to technical changes



Distributed by:

Carbide Related Technologies, Inc.
355 Sackett Point Road, #5
North Haven, CT 06473
T-203-281-1266 F-203-248-9331
www.carbiderelatedtech.com
sales@carbiderelatedtech.com