

Type 1322 / 1328



End Mill - DIAMOND COATED - Two Flute -with flat-end end style

Applications / Advantages:

- Routing of inner and outer contours in IMS as well as aluminum and copper
- Ideally suited for depth controlled routing in aluminum and copper, laminate with ceramic fillers
- High dimensional accuracy and process capability
- Feed rate increases by factor 3 - 4
- Tool life increases up to 12 times
- No pre-drilling required with Type 1328



Diamond Coating - Made in Germany

Size mm	Diameter inch	Flute Length		Flute Length	
		mm	inch	mm	inch
0.20	.0079	.5	.0196	-	-
0.30	.0118	-	-	2.0	.0787
0.50	.0197	-	-	2.0	.0787
0.60	.0236	-	-	2.0*	.0787
0.80	.0315	-	-	2.0*	.0787
1.00	.0394	-	-	3.0*	.118
1.20	.0472	-	-	3.0*	.118
1.30	.0512	-	-	3.0	.118
1.40	.0551	-	-	3.0	.118
1.50	.0591	3.0*	.118		
1.50	.0591			5.0	.197
1.60	.0630	-	-	5.0*	.197
1.80	.0709	-	-	5.0*	.197
1.90	.0748	-	-	5.0*	.197
2.00	.0787	4.0*	.157		
2.00	.0787			6.0*	.236
2.10	.0827	-	-	6.0	.236
2.40	.0945	-	-	6.0*	.236
2.50	.0984	-	-	6.0	.236
3.00	.1181	-	-	6.0*	.236

* Additional sizes and flute lengths made to order.

Geometry: 1322

- Right hand spiral, right hand cut (up cut)
- Flat end end style
- Shank diameter .1250" and over-all-length is 1.500"
- Tolerance according to router specifications
- Made of solid carbide

Geometry: 1328

- Available range 1.50 - 3.00mm
- Center cutting
- * available ex stock



Manufactured by:

GCT, GmbH
 Josef-Bayer-Srt.3
 D-88250 Weingarten
 Germany
 Rev-02/2015

Tel. +49-(0) 751- 50 91 58 0
 Fax: +49-(0) 751-50 91 58 99
 E-Mail: info@gctool.com
www.gctool.com
 Subject to technical changes



Distributed by:

Carbide Related Technologies, Inc.
 355 Sackett Point Road, #5
 North Haven, CT 06473
 T-203-281-1266 F-203-248-9331
www.carbiderelatedtech.com
sales@carbiderelatedtech.com