

# **Drill -Standard - DIAMOND COATED**

## Applications / Advantages:

- Ideally suited for drilling of IMS, aluminum, copper, laminate with ceramic fillers and high Tg materials as RO4003/4350, Arlon 25x, Isola IS 620
- Suited for drilling of glass, quartz, ceramic (Al<sub>2</sub>O<sub>3</sub>, AIN, ZrO<sub>2</sub> and SiC) and silicon
- High drill quality and process capability
- Feed rate increases by factor of 3 4
- Tool life increases by up to 20 times



DIAMOND COATING - Made in Germany

#### Flute Length Size Diameter inch mm inch mm 1.30 .0512 7.0 .276 7.0 1.35 .0531 .276 1.40 .0551 7.0 .276 : : 1.90 .0748 7.0 .276 1.95 276 .0768 7.0 2.00 .0787 9.0 354 2.05 .0807 9.0 354 : 3.10 .1220 9.0 354 3.15 .1240 9.0 354 3.175 .1250 9.0 .354

#### Geometry: 1835

- Right hand spiral, right hand cut (up cut)
- Shank diameter .1250" and over-all-length is 1.500"
- Tolerances according to drill specifications.
- Made of solid carbide.

## Manufactured by:

GCT, GmbH Josef-Bayer-Srt.3 D-88250 Weingarten Germany

Tel. +49-(0) 751- 50 91 58 0 Fax: +49-(0) 751-50 91 58 99 E-Mail: info@gctool.com www.gctool.com Rev- 02/2015 Subject to technical changes



### Distributed by:

Carbide Related Technologies, Inc. 355 Sackett Point Road, #5 North Haven, CT 06473 T-203-281-1266 F-203-248-9331 www.carbiderelatedtech.com sales@carbiderelatedtech.com

Additional sizes and flute lengths made to order.