

Type **1200**

Router - DIAMOND COATED - Diamond Cut

Applications / Advantages:

- Routing of inner and outer contours as well as for depanelizing of assembled PCB's
- Especially suited for routing of high Tg up to 185° C and laminates with fillers
- High dimensional accuracy and process capability



Diamond Coating - Made in Germany

Size mm	Diameter inch	Flute Lengths			
		mm	inch	mm	inch
.80	.0315	4.0	.157	5.0	.197
.95	.0374	-	-	5.5	.217
1.00	.0394	5.2	.204	6.5	.256
1.10	.0433	-	-	6.5	.256
1.20	.0472	-	-	7.0	.276
1.27	.0500	5.0	.197	-	-
1.30	.0512	-	-	7.0	.276
1.40	.0551	-	-	7.0	.276
1.50	.0591	7.5	.295	8.5	.335
1.60	.0630	7.5	.295	8.5	.335
1.70	.0669	-	-	8.5	.335
1.80	.0709	-	-	8.5	.335
2.00	.0787	9.0	.354	10.0	.394
2.30	.0906	9.0	.354	-	-
2.40	.0945	9.0	.354	10.0	.394
2.50	.0984	9.0	.354	-	-
2.55	.1004	-	-	10.0	.394
2.80	.1102	9.0	.354	-	-
2.90	.1142	9.0	.354	-	-
3.00	.1181	-	-	10.0	.394
3.175	.1250	-	-	10.0	.394

* Additional sizes and flute lengths made to order.

Geometry: 1200

- Right hand spiral, right hand cut (up cut)
- Fishtail end style
- Shank diameter .1250" and over-all-length is 1.500"
- Tolerance according to router specifications
- Made of solid carbide

Manufactured by:

GCT, GmbH
 Josef-Bayer-Srt.3
 D-88250 Weingarten
 Germany
 Rev-02/2015

Tel. +49-(0) 751- 50 91 58 0
 Fax +49-(0) 751-50 91 58 99
 E-Mail: info@gctool.com
www.gctool.com
 Subject to technical changes



Distributed by:

Carbide Related Technologies, Inc.
 355 Sackett Point Road, #5
 North Haven, CT 06473
 T-203-281-1266 F-203-248-9331
www.carbiderelatedtech.com
sales@carbiderelatedtech.com