Single flute end mill - DIAMOND COATED

Applications / Advantages:

- Routing of inner and outer contours of IMS made copper
- Very good edge surface quality
- Very high dimensional accuracy and process capability
- Feed rate increases by factor 3 4
- Tool life increases up to 12 times

Type 1312



Type 1318



Size	Diameter	Type 1312 Flute Length				Type 1318 Flute Length	
mm	inch	mm	inch	mm	inch	mm	inch
.80	.0315	2.0	.078		-	-	-
1.00	.0394	3.0	.118		-	-	-
1.20	.0472	3.0	.118		-	-	-
1.40	.0551	3.0	.118		-	-	-
1.60	.0630	4.0	.157	-	-	-	-
1.80	.0709	4.0	.157	-	-	-	-
2.00	.0787	4.0	.157	6.0	.236	5.0	.197
2.40	.0945	-	-	6.0	.236	-	-
3.00	.1181	-	-	6.0	.236	5.0	.197

^{*} Additional sizes and flute lengths made to order.

Type: 1312

- Right hand cutting, right twisted (up cut)
- Flat end cut
- Shank Ø 3.175mm
- Overall length 38.10mm
- tolerances according to GCT router specification
- Made of solid carbide

Type 1318:

- right hand cutting, right twisted (up cut)
- shank Ø 6.0mm
- overall length 40.0mm
- tolerances according to GCT router specification
- made of solid carbide

Manufactured by:

GCT, GmbH Josef-Bayer-Srt.3 D-88250 Weingarten Germany

Rev-04/2022

Tel. +49-(0) 751- 50 91 58 0 Fax: +49-(0) 751-50 91 58 99 E-Mail: info@gctool.com www.gctool.com

Subject to technical changes



Distributed by:

Carbide Related Technologies, Inc. 355 Sackett Point Road, #5 North Haven, CT 06473 T-203-281-1266 F-203-248-9331

www.carbiderelatedtech.com