

Type 1534

Drill -Inverse Diameter - DIAMOND COATED

Applications / Advantages:

- Ideally suited for drilling IMS, aluminum, copper, laminate with ceramic fillers and high Tg material $\geq 200^{\circ}\text{C}$ such as RO4003/4350, Arlon 25x, Isola IS 620
- Suited for drilling of glass, quartz, ceramic (Al_2O_3 , AlN , ZrO_2 and SiC) and silicon
- High drilling quality and process capability, e.g. for X-ray drilling machine
- Feed rate increases by factor of 3 - 4 times
- Tool life increases by as much as 20 times



DIAMOND COATING - Made in Germany

Size mm	Diameter inch	Flute Length	
		mm	inch
3.20	.1260	12.0	.472
3.25	.1280	12.0	.472
3.30	.1299	12.0	.472
3.35	.1319	12.0	.472
:	:	:	:
:	:	:	:
6.25	.2461	12.0	.472
6.30	.2480	12.0	.472
6.35	.2500	12.0	.472
6.40	.2520	12.0	.472

* Additional sizes and flute lengths made to order.

Geometry: 1534

- Right hand spiral, right hand cut (up cut)
- Shank diameter .1250" and over-all-length is 1.500"
- Tolerances according to drill specifications.
- Made of solid carbide

Manufactured by:

GCT, GmbH
Josef-Bayer-Srt.3
D-88250 Weingarten
Germany
Rev- 01/2022

Tel. +49-(0) 751- 50 91 58 0
Fax: +49-(0) 751-50 91 58 99
E-Mail: info@gctool.com
www.gctool.com
Subject to technical changes



Distributed by:

Carbide Related Technologies, Inc.
355 Sackett Point Road, #5
North Haven, CT 06473
T-203-281-1266 F-203-248-9331
www.carbiderelatedtech.com