

Type

1640

Drill - Undercut - MicroSpeed Coating with optimized point geometry

Applications / Advantages:

- Suited for drilling halogene free material, laminate with fillers & high Tg $\geq 150^{\circ}$
- High drilling quality and process capability
- Tool life increases by as much as 20 times



DIAMOND COATING - Made in Germany

Size mm	Diameter inch	Flute Length			
		mm	inch	mm	inch
.20	.0079	3.5	.137	-	-
.25	.0098	3.5	.137	-	-
.30	.0118	3.5	.137	5.0	.196
.35	.0138	-	-	5.0	.196
.40	.0157	-	-	5.0	.196
.45	.0177	-	-	5.0	.196

* Additional sizes and flute lengths made to order.

Geometry: 1640

- Right hand spiral, right hand cut (up cut)
- Shank diameter .1250" and over-all-length is 1.500"
- Tolerances according to drill specifications.
- Made of solid carbide.



Manufactured by:

GCT, GmbH
Josef-Bayer-Srt.3
D-88250 Weingarten
Germany

Rev-01/2022

Tel. +49-(0) 751- 50 91 58 0
Fax +49-(0) 751-50 91 58 99
E-Mail: info@gctool.com
www.gctool.com
Subject to technical changes



Distributed by:

Carbide Related Technologies, Inc.
355 Sackett Point Road, #5
North Haven, CT 06473
T-203-281-1266 F-203-248-9331
www.carbiderelatedtech.com